INDUSTRIAL COMPONENT DATA

SACC-DSI-MS-12CON-M12 SCO SH 1437106 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-MS-12CON-M12 SCO SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-MS-12CON-M12 SCO SH
Catalog number	1437106
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-E62A672CD8
Generated	2026-11-18

Product Overview

Flush-type connector
Conect. plug. to be apar. poster wall, 12-pole, Male connector, straight, M12-SPEEDCON, coding: A, Rear mounting, M12 x 1, Soldering pins, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239645

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1437106
Packing unit 20 pc
Minimum order quantity 20 pc
Catalog page Page 249 (C-2-2013)
GTIN 4046356449618
Weight per Piece (excluding packing) 9.600 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length of the solder pin 6 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 1.5 A
Rated voltage 30 V
Rated surge voltage 0.8 kV
Number of positions 12
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Solder pins
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type Rear mounting M12 x 1 With flat nut
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Cable
Standards/specifications M12 connector IEC 61076-2-101
Ambient temperature (oper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-MS-12CON-M12 SCO SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.