INDUSTRIAL COMPONENT DATA

SACC-V-3CON-PG9/A-1L-SV 24V 1527919 PHOENIX CONTACT Valve connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-V-3CON-PG9/A-1L-SV 24V



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-V-3CON-PG9/A-1L-SV 24V
Catalog number	1527919
Category	Valve connector (field assembly)
Minimum order	1 Pcs
Document ID	EO-FABCFA0DC1
Generated	2026-11-18

Product Overview

Valve connectors
Valve Connector, Universal, 3-Pole, Valve Connector A, Screw Connection, Pg9 Cable Gland, Cable Outer Diameter 6 mm ... 8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data
Orderkey 1527919
Packing unit 1 pc
Catalog page Page 110 (PC-2009)
GTIN 4017918980993
Weight per Piece (excluding packing) 24.700 g
Custom tariff number 85366990
Country of origin HU (Hungary)
Dimensions
External diameter 6 mm ... 8 mm
Stripping length of the sheath 34 mm (PE cable)
27 mm (Contact 2)
24 mm (Contact 2)

Stripping length of the individual wire 6 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (valve plug)
Degree of protection IP65
General
Rated current at 40°C 10 A
Rated voltage 24 V
Number of positions 3
Color handle area transparent
Insulation resistance >= 100 M?
Status display 1 LED
Protective circuit/component Varistor
Overvoltage category II
Degree of pollution 3
Connection method Screw connection
Conductor cross section 0.34 mm² ... 1.5 mm²
Conductor cross section AWG 22 ... 16
Insertion/withdrawal cycles 50 (Valve connector)
Torque 0.8 Nm ... 1 Nm (Pressure nut)
0.4 Nm (Central screw)
0.5 Nm (Contact screw)
Material
Flammability rating according to UL 94 HB
Valve plug contact material CuSn
Valve plug contact surface material Ni
Valve plug contact insert material PA6
Material housing valve plug PA6
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-V-3CON-PG9/A-1L-SV 24V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.