INDUSTRIAL COMPONENT DATA

VS-15-ST-DSUB-2P-5S-LH 1655360 PHOENIX CONTACT D-SUB combination contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-15-ST-DSUB-2P-5S-LH



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-15-ST-DSUB-2P-5S-LH
Catalog number	1655360
Category	Contact insert for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-531F39BE58
Generated	2026-11-18

Product Overview

D-SUB combination contact insert
Combined contact insert D-SUB, number of poles: 7, material: Steel, tin-plated, connection type: Weld connection, housing size: 2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1655360
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 215 (C-2-2013)
GTIN 4046356029292
Weight per Piece (excluding packing) 11.970 g
Custom tariff number 85366990
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 7
Connection profile D-SUB 15

Insertion/withdrawal cycles >= 200
Connection method Solder connection
Insertion force per signal contact <= 3.40 N
Extraction force per signal contact >= 0.2 N
Mounting type 4-40 UNC thread
Insulation resistance >= 5 G?
Type 15
Size of housing 2
Note The contacts must be ordered separately since they are not included in the scope of supply of the combi contact inserts.
Ambient conditions
Ambient temperature (operation) -55 °C ... 130 °C
Material data
Flammability rating according to UL 94 V0
Housing material Steel, tin-plated
Contact carrier material PBT-GF
Contact material Copper alloy
Contact surface material Gold over nickel
Electrical characteristics
Number of positions 7
Rated current 5 A (at 20°C (signal contacts))
Overvoltage category III
Degree of pollution 2
Rated voltage (III/3) 250 V
Test voltage 1200 V
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027140816eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-15-ST-DSUB-2P-5S-LH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.