INDUSTRIAL COMPONENT DATA

# VS-25-ST-DSUB-3P-10S-LH 1655425 PHOENIX CONTACT D-SUB combination contact insert

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-25-ST-DSUB-3P-10S-LH**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VS-25-ST-DSUB-3P-10S-LH |
| Catalog number | 1655425 |
| Category | Contact insert for rectangular connectors |
| Minimum order | 10 Pcs |
| Document ID | EO-8F40291D65 |
| Generated | 2026-11-18 |

## Product Overview

D-SUB combination contact insert
Combined contact insert D-SUB, number of poles: 13, material: Steel, tin-plated, connection type: Weld connection, housing size: 3

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1655425
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 215 (C-2-2013)
GTIN 4046356029353
Weight per Piece (excluding packing) 15.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 13
Connection profile 25-pos. D-SUB

Insertion/withdrawal cycles >= 200
Connection method Solder connection
Insertion force per signal contact <= 3.40 N
Extraction force per signal contact >= 0.2 N
Mounting type 4-40 UNC thread
Insulation resistance >= 5 G?
Type 25
Size of housing 3
Note The contacts must be ordered separately since they are not included in the scope of supply of the combi contact inserts.
Ambient conditions
Ambient temperature (operation) -55 °C ... 130 °C
Material data
Flammability rating according to UL 94 V0
Housing material Steel, tin-plated
Contact carrier material PBT-GF
Contact material Copper alloy
Contact surface material Gold over nickel
Electrical characteristics
Number of positions 13
Rated current 5 A (at 20°C (signal contacts))
Overvoltage category III
Degree of pollution 2
Rated voltage (III/3) 250 V
Test voltage 1200 V
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.02714081...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-25-ST-DSUB-3P-10S-LH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.