
INDUSTRIAL COMPONENT DATA

# VC-TR3/4M-PEA-S8888-SET 1607263 PHOENIX CONTACT Contact insert set

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VC-TR3/4M-PEA-S8888-SET**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VC-TR3/4M-PEA-S8888-SET |
| Catalog number | 1607263 |
| Category | Contact insert for rectangular connectors |
| Minimum order | 5 Pcs |
| Document ID | EO-73B4482510 |
| Generated | 2026-11-18 |

## Product Overview

Contact insert set
Contact holder set for aerial side, bobbin frame with PE, 4 fixing screws, pre-assembled 8-pole contact holders, 6 encoder pins

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1607263
Packing unit 5 pc
Catalog page Page 32 (C-2-2013)
GTIN 4017918941017
Weight per Piece (excluding packing) 45.570 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Connection technology Screw connection
Connection method Screw connection
Tightening torque 0.2 Nm ... 0.25 Nm
Degree of pollution 3

Number of positions 31+PE
Insertion/withdrawal cycles >= 100
Size VC3
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 0.75 mm²
Conductor cross section 0.14 mm² ... 1.5 mm²
Ambient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Material data
Housing material PA
Contact material CuZn
Contact surface material Tin-plated
Contact carrier material PA
Electrical characteristics
Rated voltage (III/3) 160 V
Nominal voltage UN 160 V
Rated surge voltage 2.5 kV
2.5 kV
Rated current 10 A
10 A
Nominal current IN 10 A
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440205eCl@ss 8.027440205eCl@ss 9.027440205
ETIM 2.0EC001121ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC00...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VC-TR3/4M-PEA-S8888-SET with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.