INDUSTRIAL COMPONENT DATA

VS-BH-M12FSX-10G-RJ45/180 1404549 PHOENIX CONTACT Control cabinet feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-BH-M12FSX-10G-RJ45/180



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-BH-M12FSX-10G-RJ45/180
Catalog number	1404549
Category	Fibre optic attenuator
Minimum order	1 Pcs
Document ID	EO-0B6399C057
Generated	2026-11-19

Product Overview

Control cabinet feed-through
Control cabinet feedthrough, M12, 8 poles, X-coded to RJ45 female connector, 180° female input, IP65/67

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1404549
Packing unit 1 pc
Catalog page Page 347 (C-2-2017)
GTIN 4046356699426
Weight per Piece (excluding packing) 36.500 g
Custom tariff number 85366990
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 8
Number of slots 1
Shielded yes
Insertion/withdrawal cycles >= 100
Cable outlet straight

Color black
Mounting type Rear mounting
Degree of protection IP65/IP67
Type Straight
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C
Ambient temperature (storage/transport) -25 °C ... 85 °C
Degree of protection IP65
IP67
Material data
Flammability rating according to UL 94 V0
Housing material PA
Contact material Copper alloy
Electrical characteristics
Number of positions 8
Nominal voltage UN 60 V
Nominal current IN 0.5 A
Transmission characteristics (category) CAT6A
GRP transmission properties Ethernet CAT6ACAT6A
Transmission speed 10 Gbps
Rated current 1.75 A
Rated voltage (III/3) 72 V (DC)
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440312eCl@ss 8.027440312eCl@ss 9.027440312
ETIM 4.0EC001121ETIM 5.0EC002641ETIM 6.0EC002641
UNSPSC 6.0131261501UNSPSC 7.090131261501U...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-BH-M12FSX-10G-RJ45/180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.