INDUSTRIAL COMPONENT DATA

HC-STA-B16-CHWS-1TTM32-ELC-AL 1412646 PHOENIX CONTACT Coupling housings B16, With single locking latch, Mate..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B16-CHWS-1TTM32-ELC-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-B16-CHWS-1TTM32-ELC-AL
Catalog number	1412646
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-5017DE5E28
Generated	2026-11-18

Product Overview

Coupling housings B16, With single locking latch, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, straight, Height: 79 mm, Cable gland: none, Gland: no, 1x M32, Standard
B16 coupling housing, with longitudinal flange, material: Die-cast aluminum, seawater resistant, cable outlets: 1, straight, 1x M32, height: 79 mm, cable gland: without, Standard
Coupling housings B16, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, 1x M32, height: 79 mm, cable gland: none, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K
Product propertiesProduct type Housing with locking latch
Housing type Coupling housings
Application Standard
Type B16
No. of cable outlets 1
Type of the screw connection 1x M32
Type Tall design

Cable outlet straight
Pg screw connection none
Data management status
Article revision 03
DimensionsDimensional drawing
Width 44 mm
Height 79 mm
Length 93.5 mm
Material specificationsFlammability rating according to UL 94 V0 (Interlock)
Seal material NBR, conductive
Housing material Die-cast aluminum, salt water resistant
Housing surface material uncoated
Locking latch material PA
Mechanical propertiesMechanical data
Type of the screw connection 1x M32
Locking type Latch
Environmental and real-life conditionsAmbient conditions
Degree of protection IP66
IP67
Enclosure rating (NEMA) 4 (UL 50e)
4X (UL 50e)
12 (UL 50e)
Impact strength IK08
Ambient temperature (operation) -40 °C ... 125 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B16-CHWS-1TTM32-ELC-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.