INDUSTRIAL COMPONENT DATA

HC-COM- 8-EBUC 1408494 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-COM-8-EBUC



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-COM-8-EBUC
Catalog number	1408494
Category	Contact insert for rectangular connectors
Minimum order	2 Pcs
Document ID	EO-E5979AFE5F
Generated	2026-11-18

Product Overview

Contact insert
Contact insert, number of poles: 8+PE, size: COM, power contacts: 8, control contacts: 0, Female, Crimped connection, 500 V, 16 A, 0.5 mm² ... 4 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1408494
Packing unit 2 pc
Minimum order quantity 2 pc
Note Made to Order (non-returnable)
Catalog page Page 649 (C-2-2017)
GTIN 4046356618205
Weight per Piece (excluding packing) 16.350 g
Custom tariff number 85366990
Country of origin CN (China)
General
Note For crimp contacts CK2,5-ED...
Connection method Crimp connection
Degree of pollution 3

Overvoltage category III
Number of positions 8+PE
No. of power contacts 8
No. of control contacts 0
Insertion/withdrawal cycles >= 500
Size COM
Contact numbering 1 - 8
Conductor cross section 0.5 mm² ... 4 mm²
Connection cross section AWG 20 ... 12
Stripping length of the individual wire 7.5 mm
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Ambient conditions
Ambient temperature (operation) -40 °C ... 100 °C (including heating up of contacts)
Material data
Contact material Copper alloy
Contact surface material Ag (alternatively Au)
Contact carrier material PC
Electrical characteristics
Rated voltage for power contacts 500
Rated voltage (III/3) 500 V
Rated surge voltage 6 kV
Rated current 16 A
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.0272612...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-COM-8-EBUC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.