

## INDUSTRIAL COMPONENT DATA

# CSD-SL 200S GN 2404768 PHOENIX CONTACT Signal light, 24 V DC, green, communication interface, safe diagnosti..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CSD-SL 200S GN



|                 |                                                                     |
|-----------------|---------------------------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                                     |
| MPN / Reference | CSD-SL 200S GN                                                      |
| Catalog number  | 2404768                                                             |
| Category        | Accessories/spare parts for optic and acoustic signalling equipment |
| Minimum order   | 1 Pcs                                                               |
| Document ID     | EO-9724287495                                                       |
| Generated       | 2026-09-29                                                          |

## Product Overview

Signal light, 24 V DC, green, communication interface, safe diagnostics in accordance with safety standards

Signal light, 24 VDC, IALA green Optimum, diameter: 174 mm, protection index: IP65/IP67, Communication interface, Safe diagnostics

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | PHOENIX CONTACT > Safety |
|--------------|--------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2404768

Packing unit 1

Catalog page Page 511 (C-6-2019)

GTIN 4055626447247

Custom tariff number 85308000

Dimensions

General

Light properties

Environmental Product Compliance

Ambient conditions

Power supply for module electronics

Standards and Regulations

**Classifications****Dimensions**

Width 174 mm

Height 189 mm

Depth 66 mm

Length 174 mm

Back to topAmbient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Air pressure (operation) 70 hPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 hPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP65/IP67, when installed

Back to topGeneral

Net weight 1680 g

Diagnostics messages LEDs; temperature, current, voltage, etc. Yes

Mains failure, communication failure Yes

Safe diagnostics (up to SIL 2/PL d) in conjunction with safe modules (safety technology) Yes

Mounting position vertical

Design Operating hours counter

Inrush current max. 12 A (μ-sec-pulse)

Back to topPower supply for module electronics

Connection method M12 connector

Number of positions 8

Supply voltage 24 V DC (DC)

Supply voltage range 19.2 V DC ... 30 V DC (DC)

Current consumption max. 740 mA (green LEDs)

Power consumption typ. 14 W (green LEDs)

Back to topLight properties

Source of light type LED

Number of LEDs 8 (according to IALA recommendation E200-1 and CIE 1931)

Service life, lighting appliance 50000 h

Light color IALA green, optimu...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / CSD-SL 200S GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.