INDUSTRIAL COMPONENT DATA

CSD-SL 300 GN 30X30 1051088 PHOENIX CONTACT Signal lamp

Brand: PHOENIX CONTACT | Manufacturer Part Number: CSD-SL 300 GN 30X30



Manufacturer	PHOENIX CONTACT
MPN / Reference	CSD-SL 300 GN 30X30
Catalog number	1051088
Category	Monitored LED indicator luminaire
Minimum order	1 Pcs
Document ID	EO-AA5E89ED8D
Generated	2026-11-19

Product Overview

Signal lamp
Signal light, 24 VDC, IALA green Optimum, emission angle: 30 °, diameter: 272 mm, protection index: IP65/IP67, Communication interface

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data
Orderkey 1051088
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626670638
Weight per Piece (excluding packing) 3,860.000 g
Custom tariff number 85308000
Country of origin DE (Germany)
Dimensions
Width 272 mm
Height 291 mm
Depth 68 mm
Length 272 mm

Ambient conditions
Ambient temperature (operation) -25 °C ... 55 °C
Ambient temperature (storage/transport) -25 °C ... 85 °C
Air pressure (operation) 70 hPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 hPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP65/IP67, when installed
General
Assembly instructions Use of stainless steel fittings (corrosion-resistant)
Net weight 3860 g
Diagnostics messages LEDs; temperature, current, voltage, etc. Yes
Mains failure, communication failure Failsafe
Design Operating hours counter
Inrush current max. 36 A ()
Power supply for module electronics
Connection method M17 hybrid connectors with SPEEDCON locking system
Number of positions 8
Supply voltage 24 V DC (DC)
Current consumption max. 2.73 A (green LEDs)
Power consumption max. 75 W (green LEDs)
Light properties
Source of light type LED
Number of LEDs 30 (according to IALA recommendation E200-1 and CIE 1931)
Service life, lighting appliance 50000 h
Light color IALA green, optimum
Color temperature / wavelength 490...510 nm
Color class C3 (EN 12966)
Luminance L3 (EN 12966)
Luminance ratio R3 (EN 12966)
Phantom light class 5 (EN 12368)
Luminous intensity 6800 C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CSD-SL 300 GN 30X30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.