

INDUSTRIAL COMPONENT DATA

CUC-DSI-S1STZ-S/DSLKC1P20S 1418758 PHOENIX CONTACT D-SUB contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-DSI-S1STZ-S/DSLKC1P20S



Manufacturer	PHOENIX CONTACT
MPN / Reference	CUC-DSI-S1STZ-S/DSLKC1P20S
Catalog number	1418758
Category	D-Sub connector
Minimum order	10 Pcs
Document ID	EO-D09F3D1BCF
Generated	2026-09-23

Product Overview

D-SUB contact insert

D-SUB contact insert, with 20 warning contacts and 1 power contact, with solder cups, straight, male connector, 3 mm hole attachment

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1418758

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626150192

Weight per Piece (excluding packing) 17.060 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Standards/specifications DIN 41652

Number of positions 21

Insertion/withdrawal cycles >= 200

Connection method Solder cups
Insertion force per signal contact ≤ 3.40 N
Mounting type 3 mm hole
Type of note Notes on operation
Note Power contacts must be ordered separately
Ambient conditions
Ambient temperature (operation) $-55\text{ }^{\circ}\text{C} \dots 130\text{ }^{\circ}\text{C}$
Material data
Flammability rating according to UL 94 V0
Housing material Steel, tin-plated
Contact carrier material Polyester GF
Contact material Copper alloy
Contact surface material Gold over nickel
Electrical characteristics
Number of positions 21
Rated current 5 A
Degree of pollution 1
Rated voltage (III/3) 400 V
Standards and Regulations
Standards/regulations DIN 41652
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440302eCl@ss 8.027440302eCl@ss 9.027440302
ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000438ETIM 5.0EC001132ETIM 6.0EC001132
UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12.0139121522UN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-DSI-S1STZ-S/DSLKC1P20S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.