INDUSTRIAL COMPONENT DATA

CUC-F-D1ZNI-S/R4GCHP8 1086111 PHOENIX CONTACT RJ45 coupling, degree of protection: IP20, number of positions..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CUC-F-D1ZNI-S/R4GCHP8



Manufacturer	PHOENIX CONTACT
MPN / Reference	CUC-F-D1ZNI-S/R4GCHP8
Catalog number	1086111
Category	Fibre optic attenuator
Minimum order	1 Pcs
Document ID	EO-25B6B12CA9
Generated	2026-11-19

Product Overview

RJ45 coupling, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6
RJ45 coupling, protection index: IP20, number of poles: 8, 10 GBit/s, CAT6A, material: Metal, connection type: 2x RJ45, Freenet model for use with IP67 recessed frames and terminal outputs

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1086111
Packing unit 1 pc
GTIN 4055626877129
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85366930
Country of origin PL (Poland)
Drawings
Ambient conditions
Electrical characteristics
Classifications
Mechanical characteristics
Material data

Standards and Regulations
Drawings
Dimensional drawing
Back to topMechanical characteristics
Connection method 2x RJ45
Number of slots 2
Transmission speed 10 Gbps
Transmission characteristics (category) CAT6A
Back to topAmbient conditions
Ambient temperature (operation) -10 °C ... 60 °C
Degree of protection IP20
Back to topMaterial data
Contact surface material Gold over nickel
Contact material Spring steel
Housing material Zinc die-cast
Housing surface material metal-plated
Back to topElectrical characteristics
Number of positions 8
GRP transmission properties CAT6AIn accordance with ISO/IEC 11801
Transmission speed 10 Gbps
Frequency range 500 MHz
Dielectric strength > 1000 V DC
Contact resistance 200 m? (Trunk in to trunk out)
Rated voltage (III/3) 72 V (DC)
Back to topStandards and Regulations
Standards/specifications IEC 60603-7 DIN EN 50173-1 ISO/IEC 11801-Am.1 IEC 60068-2
Back to topClassifications
eCl@ss
eCl@ss 10.0.1 19179290
eCl@ss 8.0 19179290
eCl@ss 9.0 19179290
Back to topETIM
ETIM 5.0 EC001134
ETIM 6.0 EC000310
ETIM 7.0 EC000310
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CUC-F-D1ZNI-S/R4GCHP8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.