INDUSTRIAL COMPONENT DATA

# D-PTC 2,5-QUATTRO-MT 3270103 PHOENIX CONTACT End cover

**Brand: PHOENIX CONTACT | Manufacturer Part Number: D-PTC 2,5-QUATTRO-MT**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | D-PTC 2,5-QUATTRO-MT |
| Catalog number | 3270103 |
| Category | Endplate and partition plate for terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-9215F55D7B |
| Generated | 2026-11-18 |

## Product Overview

End cover
End cap, length: 79.6 mm, width: 2.2 mm, height: 29 mm, colour: grey
End cover, depth: 29 mm, width: 2.2 mm, height: 79.6 mm, colour: grey

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3270103
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356960588
Weight per Piece (excluding packing) 3.050 g
Custom tariff number 85389099
Country of origin CN (China)
General
Color gray
Material PA
Flammability rating according to UL 94 V0
Dimensions

Width 2.2 mm
End cover width 2.2 mm
Length 79.6 mm
Height 29 mm
Height NS 35/7,5 36.5 mm
Height NS 35/15 44 mm
General
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Standards and Regulations
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 H...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D-PTC 2,5-QUATTRO-MT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.