

INDUSTRIAL COMPONENT DATA

VS-25-ST-DSUB-CD-B 1689954 PHOENIX CONTACT D-SUB contact support

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-25-ST-DSUB-CD-B



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-25-ST-DSUB-CD-B
Catalog number	1689954
Category	D-Sub connector
Minimum order	100 Pcs
Document ID	EO-FA280D57F3
Generated	2026-09-22

Product Overview

D-SUB contact support

D-SUB contact holder, wrap size 3, for 25 signal contacts, male contact type, for crimped contacts, straight, 3 mm drill fixing, for recessed frame and VS-25 overhead housing-...

D-SUB contact insert, tab size 3, for 25 signal contacts, plug type, for crimp contacts, straight, 3 mm hole fixing, for VS-25 flush and mobile frames-...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1689954

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 212 (C-2-2013)

GTIN 4017918914356

Weight per Piece (excluding packing) 14.460 g

Custom tariff number 85366990

Country of origin DE (Germany)

Mechanical characteristics

Number of positions 25
Connection profile 25-pos. D-SUB
Insertion/withdrawal cycles ≥ 500
Connection method Crimp connection
Insertion force per signal contact ≤ 3.40 N
Mounting type Hole
Type 25
Size of housing 3
Ambient conditions
Ambient temperature (operation) -55 °C ... 130 °C
Material data
Flammability rating according to UL 94 V0
Housing material Steel, tin-plated
Contact carrier material Glass-fiber reinforced thermoplastics, UL 94 V0
Electrical characteristics
Number of positions 25
Rated current 5 A (at 20 °C)
Overvoltage category III
Degree of pollution 2
Rated voltage (III/3) 125 V
Test voltage 1200 V
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss
7.027440302eCl@ss 8.027440302eCl@ss 9.027440205
ETIM 2.0EC000437ETIM 3.0EC000437ETIM 4.0EC000438ETIM 5.0EC001132ETIM 6.0EC000438
UNSPSC 6.0130211923UNSPSC 7.090139121522UNSPSC 1139121522UNSPSC 12.0139121522UNSPSC
13.239121522

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-25-ST-DSUB-CD-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.