INDUSTRIAL COMPONENT DATA

# VS-15-BU-DSUB-HD-EG 1655166 PHOENIX CONTACT D-SUB contact insert

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-15-BU-DSUB-HD-EG**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VS-15-BU-DSUB-HD-EG |
| Catalog number | 1655166 |
| Category | D-Sub connector |
| Minimum order | 10 Pcs |
| Document ID | EO-C582B9AF18 |
| Generated | 2026-11-18 |

## Product Overview

D-SUB contact insert
D-SUB contact insert, wrap size 2, with 26 signal contacts, female contact type, with solder cup, straight, 3 mm hole fixing, for VS-15 recessed frames and bobbin housings-...

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1655166
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 210 (C-2-2013)
GTIN 4046356029100
Weight per Piece (excluding packing) 10.150 g
Custom tariff number 85366990
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 26
Connection profile D-SUB 15

Insertion/withdrawal cycles >= 50
Connection method Solder cup
Conductor cross section 0.34 mm²
Connection cross section AWG 22
Insertion force per signal contact <= 3.40 N
Mounting type Hole
Type 15
Size of housing 2
Ambient conditions
Ambient temperature (operation) -55 °C ... 105 °C
Material data
Flammability rating according to UL 94 V0
Contact carrier material Glass-fiber reinforced thermoplastics, UL 94 V0
Contact material Copper alloy
Contact surface material Au/Sn
Electrical characteristics
Number of positions 26
Rated current 3 A (at 20 °C)
Overvoltage category III
Degree of pollution 2
Rated voltage (III/3) 60 V
Test voltage 1000 V
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440302eCl@ss 8.027440302eCl@ss 9.027440205
ETIM 2.0EC000438ETIM 3.0EC000438ETIM 4.0EC000438ETIM....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-15-BU-DSUB-HD-EG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.