INDUSTRIAL COMPONENT DATA

# D-UTTB 4 HV 3000709 PHOENIX CONTACT End cover

**Brand: PHOENIX CONTACT | Manufacturer Part Number: D-UTTB 4 HV**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | D-UTTB 4 HV |
| Catalog number | 3000709 |
| Category | Endplate and partition plate for terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-8B468AF73C |
| Generated | 2026-11-18 |

## Product Overview

End cover
End cap, length: 75.6 mm, width: 2.2 mm, height: 57.5 mm, colour: grey
End cover, depth: 57.5 mm, width: 2.2 mm, height: 75.6 mm, color: gray

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Technical dataProduct propertiesProduct type End cover
Data management status
Article revision 01
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (operation) 20 % ... 90 %
Permissible humidity (storage/transport) 30 % ... 70 %
Material specificationsColor gray (RAL 7042)
Flammability rating according to UL 94 V0
Static insulating material application in cold -60 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
DimensionsWidth 2.2 mm
Height 75.6 mm
Depth 57.5 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D-UTTB 4 HV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.