INDUSTRIAL COMPONENT DATA

D3PC-MP 1.25-2.2-F-SN-L 1340365 PHOENIX CONTACT Crimp Contact, Rated Current: 8 A, Surface Contacts: Tin

Brand: PHOENIX CONTACT | Manufacturer Part Number: D3PC-MP 1.25-2.2-F-SN-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	D3PC-MP 1.25-2.2-F-SN-L
Catalog number	1340365
Category	Accessories/spare parts for industrial connectors
Minimum order	200 Pcs
Document ID	EO-324358A7D8
Generated	2026-11-18

Product Overview

Crimp Contact, Rated Current: 8 A, Surface Contacts: Tin
Crimped contact
Crimp contact, nominal current: 8 A, contact surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Crimp contact
Product family D3PC-MP-F
Pitch 0 mm
Connection dataStripping length 4.5 mm
Conductor cross section AWG 16 ... 14
Material specificationsContact surface Tin Sn
Contact surface material Tin
Metal surface terminal point (top layer) Tin (1 - 3 µm Sn)
Metal surface contact area (top layer) Tin (1 - 3 µm Sn)
DimensionsPitch 0 mm
Electrical propertiesNominal current IN 8 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D3PC-MP 1.25-2.2-F-SN-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.