INDUSTRIAL COMPONENT DATA

CA-12P2N8AAD00 1621739 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-12P2N8AAD00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-12P2N8AAD00
Catalog number	1621739
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-C0E7996901
Generated	2026-11-18

Product Overview

Device connector, front mounting
M23, Conect. plug. to be apar. front wall, RC, Swivel angle, shielded: yes, for standard lock and SPEEDCON, No. of poles: 12, Direction of rotation: Counter movement, contact type: Male, Crimped connection, Axial O-ring, 4x Ø 3.2, coding:N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1621739
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626000558
Weight per Piece (excluding packing) 111.110 g
Custom tariff number 85366990
Country of origin DE (Germany)
Data of the insulating body
Note Order information: Order crimp contacts Ø 1 mm separately
Coding N
Insulator material PA 6.6
Contact connection method Crimp connection

Type of contacts Pin
Application Signal
Number of positions 12
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Nominal voltage, power contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Overvoltage category II
Degree of pollution 3
Housing data
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking for standard and SPEEDCON interlock
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 10.0.127371392eCl@ss 5.127379100eCl@ss 6.027379200eCl@ss 7.027379201eCl@ss 8.027379201eCl@ss 9.027379201
ETIM 4.0EC002498ETIM 5.0EC002498ETIM 6.0EC002498
UNSPSC 13.239121421

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-12P2N8AAD00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.