INDUSTRIAL COMPONENT DATA

CA-17P1N8AHZ00 1619779 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-17P1N8AHZ00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-17P1N8AHZ00
Catalog number	1619779
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-FF77CEADB9
Generated	2026-11-18

Product Overview

Device connector, rear mounting
M23, Conect. plug. to be apar. poster wall, AC, straight, shielded: yes, for standard lock and SPEEDCON, No. of poles: 17, Direction of rotation: Standard, contact type: Male, Crimped connection, Axial joint, Central fixing, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1243831

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1619779
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 95 (C-2-2017)
GTIN 4046356821384
Weight per Piece (excluding packing) 43.750 g
Custom tariff number 85366990
Country of origin DE (Germany)
Temperature range
Ambient temperature (operation) -40 °C ... 125 °C
Data of the insulating body

Note Order information: Order crimp contacts Ø 1 mm separately
Coding N
Insulator material PA 6.6
Contact connection method Crimp connection
Type of contacts Pin
Application Signal
Number of positions 17
Contact diameter of signal contacts 1 mm
Litz wire cross section of signal contacts min. 0.08 mm²
Litz wire cross section of signal contacts max. 1 mm²
Nominal current per signal contact at 25°C 8 A
Nominal voltage, signal contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Housing data
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking for standard and SPEEDCON interlock
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002061ETIM 6.0E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-17P1N8AHZ00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.