INDUSTRIAL COMPONENT DATA

ST-5EP1N8AA400S 1620431 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-5EP1N8AA400S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-5EP1N8AA400S
Catalog number	1620431
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-4737DEA661
Generated	2026-11-18

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall., Swivel elbow, for standard and SPEEDCON lock, M17, number of poles: 5+PE, contact type: Pin, Axial O-ring, 4x Ø2.7, shielded: yes, flange size: 25.75 mm x 25.75 mm, protection index: IP67, number of poles: 6, connection type: Crimped connection, series: ST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1620431
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 144 (C-2-2017)
GTIN 4046356828192
Weight per Piece (excluding packing) 82.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Note Order information: Order 6 x Ø 1 mm crimp contacts separately
Type of locking for standard and SPEEDCON interlock

Direction of rotation of contact chamber numbering Standard
Coding N
Contact connection method Crimp connection
Type of contacts Pin
Number of positions 6
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 14 A
Contact diameter of signal contacts 1 mm
Pg housing screw connection none
Mounting type 4x Ø2,7
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 630 V
Rated surge voltage of power contacts 6 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC002635ETIM 5.0EC002061ETIM 6.0EC002061
UNSPSC 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-5EP1N8AA400S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.