INDUSTRIAL COMPONENT DATA

RF-17S1N8AAD00 1607345 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: RF-17S1N8AAD00



Manufacturer	PHOENIX CONTACT
MPN / Reference	RF-17S1N8AAD00
Catalog number	1607345
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-F9BAEE323C
Generated	2026-11-18

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall, Swivel angle, Screw lock, M23, number of poles: 17, contact type: Female, Axial O-ring, 4x Ø 3.2, shielded: yes, flange measurement: 26mm x 26mm, protection index: IP67, number of poles: 17, connection type: Crimped connection, series: RF
Front Appliance Connector, Angled, Swivel, Screw Locking, M23, Number of Poles: 17, Contact Connection Type: Female, Axial O-Ring, 4x Ø 3.2, Shielded: Yes, Flange Size: 26 mm x 26 mm, Number of Poles: 17, Connection Type: Crimp Connection, Series: RF

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1607345
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 107 (C-2-2017)
GTIN 4046356269278
Weight per Piece (excluding packing) 53.670 g
Custom tariff number 85366990
Country of origin DE (Germany)

General
Note Order information: Order crimp contacts Ø 1 mm separately
Type of locking Screw locking
Direction of rotation of contact chamber numbering Standard
Coding N
Contact connection method Crimp connection
Type of contacts Socket
Number of positions 17
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 8 A
Pg housing screw connection none
Mounting type 4x Ø 3.2
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Gasket and O-ring material FPM
Specifications according to DIN EN 61984:2001
Installation height max. 2000 m
Nominal / operating voltage of power contacts 100 V
Rated surge voltage of power contacts 1.5 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Overvoltage category of signal contacts III
Degree of pollution of signal contacts 3
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.12714...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RF-17S1N8AAD00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.