INDUSTRIAL COMPONENT DATA

SFP 1-15/120AC 2920683 PHOENIX CONTACT EMC filter surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: SFP 1-15/120AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SFP 1-15/120AC
Catalog number	2920683
Category	Surge protection device for terminal equipment
Minimum order	1 Pcs
Document ID	EO-A5B8D11054
Generated	2026-11-18

Product Overview

EMC filter surge protection device
Device protection, according to type 3/class III, with mains parasitic filter against high-frequency edging voltages, for single-phase power supply networks with separate N and PE (3-conductor system: L1, N, PE), with remote indication contact.
Device protection, according to type 3 / class III, with mains filter for interference against very frequent interference voltages, for single-phase power supply networks with separate N and PE (3-conductor system: L1, N, PE), with FM contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2920683
Packing unit 1 pc
Catalog page Page 185 (C-4-2017)
GTIN 4046356158565
Weight per Piece (excluding packing) 571.280 g
Custom tariff number 85363010
Country of origin DE (Germany)
Dimensions

Height 86.6 mm
Width 112 mm
Depth 79 mm
Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -25 °C ... 70 °C
Ambient temperature (storage/transport) -25 °C ... 70 °C
Permissible humidity (operation) 5 % ... 95 %
General
EN type T3
Number of ports Two
Mode of protection L-N
L-PE
N-PE
Mounting type DIN rail: 35 mm
Color black
silver
Housing material Aluminum
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, one-piece
Number of positions 2
Surge protection fault message Optical, remote indicator contact
For country-specific use in USA, CN, BR
Protective circuit
Nominal voltage UN 120 V AC (TN)
120 V AC (TT - only in use with RCD)
120 V AC (IT)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous voltage UC 150 V AC
Rated load current IL 15 A (50 °C)
Residual current IPE <= 0.6 mA
Nominal discharge current In(8/20) µs 3 kA
Standby power consumption PC <= 7.5 VA (at UREF)
<= 10 VA (at UC)
Reference test voltage UREF 132 V AC
Combination wave UOC 6 kV (3 kA)
Voltage protection level Up <= 0.45 kV
TOV behavior at UT(L-N) 175 V AC (5 s / withstand mode)
240 V AC (5 s / safe failure mode)
208 V AC (120 min / safe failure mode)
TOV behavior at UT(L-PE) 208 V AC (5 s / withstand mode)
175 V AC (120 min / w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SFP 1-15/120AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.