
INDUSTRIAL COMPONENT DATA

DFK-PC 4/10-GF-7,62 BD-AUXS 1714129 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PC 4/10-GF-7,62 BD-AUXS



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-PC 4/10-GF-7,62 BD-AUXS
Catalog number	1714129
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-8612338C5F
Generated	2026-11-18

Product Overview

Feed-through header
Wall pass terminal, nominal section: 4 mm², color: green, nominal current: 20 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, family of articles: DFK-PC 4/.. -GF, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Direct mounting, conductor/printed circuit board connection direction: 0 °, number of solder pins per potential: 1, plug-in system: COMBICON PC 4, Plug-in face orientation: Standard, lock: Screw lock, Attachment Type: Overhead Clamping (Thread), Packing Type: Boxed Packed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1714129
Packing unit 1
GTIN 4055626354736
Custom tariff number 85366990
Dimensions
Length [l] 32 mm
Width [w] 97.82 mm
Height [h] 30.5 mm

Pitch 7.62 mm
Dimension a 68.58 mm
General
Range of articles DFK-PC 4/..-GF
Number of positions 10
Connection method Screw connection with tension sleeve
Insulating material group I
Rated voltage (III/2) 630 V
Nominal current IN 20 A
Nominal cross section 4 mm²
Flammability rating according to UL 94 V0
Screw thread M3
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 5.0EC002637ETIM 6.0EC002637

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PC 4/10-GF-7,62 BD-AUXS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.