INDUSTRIAL COMPONENT DATA

UK 5-HEDI N GY 3000752 PHOENIX CONTACT Disconnect terminal block, Connection type: Screw connection, Cross s..

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 5-HEDI N GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 5-HEDI N GY
Catalog number	3000752
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-4D520643ED
Generated	2026-11-18

Product Overview

Disconnect terminal block, Connection type: Screw connection, Cross section: 0.2 mm²
Lever-interruptible terminal block, nominal voltage: 500 V, nominal current: 16 A, connection type: Screw connection, Sizing cross-section: 1.5 mm², cross-section: 0.2 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, NS 32, color: grey/orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

General
Number of levels 1
Number of connections 2
Nominal cross section 4 mm²
Color gray/orange
Insulating material PA
Flammability rating according to UL 94 V0
General
Rated surge voltage 6 kV
Pollution degree 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1

Nominal current IN 16 A
Maximum load current 16 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel ja
Dimensions
Width 8.2 mm
Length 58 mm
Height NS 35/7,5 50 mm
Height NS 35/15 57.6 mm
Height NS 32 55 mm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 1.5 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 1.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²
2 conductors with same cross secti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 5-HEDI N GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.