
INDUSTRIAL COMPONENT DATA

RTO 5-T 3049233 PHOENIX CONTACT Test disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: RTO 5-T



Manufacturer	PHOENIX CONTACT
MPN / Reference	RTO 5-T
Catalog number	3049233
Category	Feed-through terminal block
Minimum order	25 Pcs
Document ID	EO-0BEF5F38EC
Generated	2026-11-18

Product Overview

Test disconnect terminal block
Interruptible terminal block with stud connection technology, cross-section: 0.1 - 6 mm², AWG: 26 - 10, width 16.3 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3049233
Packing unit 25 pc
Minimum order quantity 25 pc
Note Made to Order (non-returnable)
Catalog page Page 380 (C-1-2017)
GTIN 4046356140010
Weight per Piece (excluding packing) 40.610 g
Custom tariff number 85369010
Country of origin CN (China)
General
Note Note: the BE-RT... path extension is to be used for non-insulated cable lugs (see accessories).
Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 6 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 41 A (with 6 mm² conductor cross section)
Nominal current IN 41 A
Nominal voltage UN 1000 V (Rated voltage for open disconnect point 500 V)
Open side panel Yes
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Note regarding shock protection
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of tight fit on support Test passed
Tight fit on carrier NS 35
Setpoint 5 N
Result of voltage-drop test Test passed
Requirements, voltage drop <= 6,4 mV
Result of temperature-rise test Test passe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RTO 5-T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.