INDUSTRIAL COMPONENT DATA

ST 4-TG 3038367 PHOENIX CONTACT Disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 4-TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 4-TG
Catalog number	3038367
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-821AD4543B
Generated	2026-11-18

Product Overview

Disconnect terminal block
Interruptible terminal, Current and voltage are determined by the connector used., nominal voltage: 500 V, nominal current: 20 A, 1st floor, connection type: Spring connection, Dimensioning section: 2.5 mm², cross-section: 0.08 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3038367
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 178 (C-1-2017)
GTIN 4017918941239
Weight per Piece (excluding packing) 10.230 g
Custom tariff number 85369010
Country of origin TR (Turkey)
General
Number of levels 1
Number of connections 2

Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 20 A (with 6 mm² conductor cross section)
Maximum load current 20 A (with 6 mm² conductor cross section)
Nominal voltage UN 500 V (voltage is determined by the plug used)
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.08 mm² / 0.1 kg
4 mm² / 0.9 kg
6 mm2/ 1.4 kg
Tensile test result Test passed
Conductor cross section ten...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 4-TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.