INDUSTRIAL COMPONENT DATA

DMC 1,5/13-G2F-3,5-LR P26THR 1668500 PHOENIX CONTACT Printed circuit board base housing, nominal section: 1...

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMC 1,5/13-G2F-3,5-LR P26THR

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	DMC 1,5/13-G2F-3,5-LR P26THR
Catalog number	1668500
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-E4817BEB1A
Generated	2026-11-18

Product Overview

Printed circuit board base housing, nominal section: 1.5 mm2, color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Male, number of rows: 2, number of poles: 13, family of articles: DMC 1.5/.. -G2F-LR-THR, pitch: 3.5 mm, mounting: THR welding/wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of welding pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, locking: Lock and Release, clamping type: Lock & Release air clamping (thread), packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMC 1,5/13-G2F-3,5-LR P26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.