INDUSTRIAL COMPONENT DATA

DMC 1,5/ 4-G1-3,5 P26THR 1873950 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DMC 1,5/ 4-G1-3,5 P26THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	DMC 1,5/ 4-G1-3,5 P26THR
Catalog number	1873950
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-1BD12CFE80
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 2, number of poles: 4, number of connections: 8, article family: DMC 1.5/.. -G1-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON DFMC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1873950
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4055626259239
Weight per Piece (excluding packing) 2.300 g
Custom tariff number 85366930
Country of origin CN (China)
Dimensions

Length [l] 11.6 mm
Width 14.8 mm
Pitch 3.5 mm
Dimension a 10.5 mm
Width [w] 14.8 mm
Height [h] 13.4 mm
Height 10.8 mm
Length of the solder pin 2.6 mm
Pin dimensions 0.8 x 0.8 mm
Pin spacing 2.50 mm
Length 11.6 mm
General
Range of articles DMC 1,5/..-G1-THR
Insulating material group IIIa
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Nominal current IN 8 A
Insulating material LCP
Flammability rating according to UL 94 V0
Color black
Number of positions 4
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DMC 1,5/ 4-G1-3,5 P26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.