INDUSTRIAL COMPONENT DATA

DP-LPO 2,5 3270518 PHOENIX CONTACT Spacer plate, depth: 24.4 mm, width: 5.2 mm, height: 18.5 mm, number of p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-LPO 2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	DP-LPO 2,5
Catalog number	3270518
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-22432BF592
Generated	2026-11-19

Product Overview

Spacer plate, depth: 24.4 mm, width: 5.2 mm, height: 18.5 mm, number of poles: 1, color: gray
Spacer partition, length: 18.5 mm, width: 5.2 mm, height: 24.4 mm, number of poles: 1, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Partition plate
Number of positions 1
Ambient conditionsAmbient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C ()
Permissible humidity (storage/transport) 30 % ... 70 %
Material specificationsColor gray
Material PA
Flammability rating according to UL 94 V0
Static insulating material application in cold -60 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
DimensionsWidth 5.2 mm
Height 18.5 mm
Depth 24.4 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C ()
Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-LPO 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.