INDUSTRIAL COMPONENT DATA

DP-MUTTB 2,5 1462738 PHOENIX CONTACT Partition spacer, depth: 24.1 mm, width: 2.6 mm, height: 62.8 mm, colou..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-MUTTB 2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	DP-MUTTB 2,5
Catalog number	1462738
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-A1A5F77974
Generated	2026-11-18

Product Overview

Partition spacer, depth: 24.1 mm, width: 2.6 mm, height: 62.8 mm, colour: grey
Spacer partition, length: 62.8 mm, width: 2.6 mm, height: 24.1 mm, colour: grey
Spacer plate, depth: 24.1 mm, width: 2.6 mm, height: 62.8 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Partition plate
Insulation characteristics
Overvoltage category III
Ambient conditionsAmbient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (storage/transport) 30 % ... 70 %
Material specificationsColor gray
Material PA
Flammability rating according to UL 94 V0
Insulating material group I
Insulating material PA

DimensionsWidth 2.6 mm
Height 62.8 mm
Depth 24.1 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-MUTTB 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.