INDUSTRIAL COMPONENT DATA

DP-PTRV 4/LB YE 1091504 PHOENIX CONTACT Septum spacer, length: 63,6 mm, width: 8.3 mm, height: 54 mm, color:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-PTRV 4/LB YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	DP-PTRV 4/LB YE
Catalog number	1091504
Category	Endplate and partition plate for terminal block
Minimum order	10 Pcs
Document ID	EO-F24AC4BC7A
Generated	2026-11-19

Product Overview

Septum spacer, length: 63,6 mm, width: 8.3 mm, height: 54 mm, color: yellow
Spacer partition, length: 63.6 mm, width: 8.3 mm, height: 54 mm, colour: yellow
Spacer plate, depth: 54 mm, width: 8.3 mm, height: 63.6 mm, color: yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Partition plate
Data management status
Article revision 01
Material specificationsColor yellow (RAL 1018)
Material PA
Flammability rating according to UL 94 V2
DimensionsWidth 8.3 mm
Height 63.6 mm
Depth 54 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 105 °C

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-PTRV 4/LB YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.