INDUSTRIAL COMPONENT DATA

# DP-RSCWE 6-3 3069314 PHOENIX CONTACT Spacer plate

**Brand: PHOENIX CONTACT | Manufacturer Part Number: DP-RSCWE 6-3**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | DP-RSCWE 6-3 |
| Catalog number | 3069314 |
| Category | Endplate and partition plate for terminal block |
| Minimum order | 1 Pcs |
| Document ID | EO-B91A66DD4C |
| Generated | 2026-11-19 |

## Product Overview

Spacer plate
Spacer partition, length: 80.9 mm, width: 8.2 mm, height: 70.8 mm, number of poles: 1, colour: grey
Spacer plate, depth: 70.8 mm, width: 8.2 mm, height: 80.9 mm, number of poles: 1, colour: grey

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Enclosures connectivity |

## Additional Product Information

Key Commercial Data
Orderkey 3069314
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 619 (C-1-2017)
GTIN 4055626157573
Weight per Piece (excluding packing) 14.100 g
Custom tariff number 85389099
Country of origin PL (Poland)
General
Number of positions 1
Color gray
Material PA
Flammability rating according to UL 94 V0

Overvoltage category III
Insulating material group I
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Dimensions
Width 8.2 mm
Length 80.9 mm
Height 70.8 mm
Standards and Regulations
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protectio...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DP-RSCWE 6-3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.