

**INDUSTRIAL COMPONENT DATA**

# DT 6/2,5-DREHSI-EX (5X20) 3073979 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DT 6/2,5-DREHSI-EX (5X20)



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | PHOENIX CONTACT           |
| MPN / Reference | DT 6/2,5-DREHSI-EX (5X20) |
| Catalog number  | 3073979                   |
| Category        | Fuse terminal block       |
| Minimum order   | 10 Pcs                    |
| Document ID     | EO-2B3ED6B0C1             |
| Generated       | 2026-09-21                |

## Product Overview

Fuse modular terminal block

Fuse terminal block, for fuse cartridge G, cross-section: 0.5-10 mm<sup>2</sup>, AWG: 20-8, width: 12.2 mm, colour: black

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3073979

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4046356343145

Weight per Piece (excluding packing) 26.980 g

Custom tariff number 85369095

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 2

Nominal cross section 2.5 mm<sup>2</sup>

Color black

Insulating material PA

Flammability rating according to UL 94 V0  
Maximum power dissipation for nominal condition 0.77 W  
Fuse G / 5 x 20  
Fuse type Glass / ceramics / ...  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Connection in acc. with standard IEC 60947-7-3  
Maximum load current 10 A (with 4 mm<sup>2</sup> conductor cross section)  
Nominal current IN 10 A  
Nominal voltage UN 500 V  
Connection in acc. with standard IEC 60947-7-1  
Maximum load current (upper level) 10 A  
Nominal current IN(upper level) 10 A  
Nominal voltage UN 500 V  
Open side panel No  
Dimensions  
Width 12.2 mm  
Length 71.5 mm  
Height NS 35/7,5 51.3 mm  
Height NS 35/15 58.8 mm  
Connection data  
Conductor cross section solid min. 0.5 mm<sup>2</sup>  
Conductor cross section solid max. 10 mm<sup>2</sup>  
Conductor cross section flexible min. 0.5 mm<sup>2</sup>  
Conductor cross section flexible max. 6 mm<sup>2</sup>  
Conductor cross section AWG min. 20  
Conductor cross section AWG max. 8  
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm<sup>2</sup>  
Condu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DT 6/2,5-DREHSI-EX (5X20) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.