INDUSTRIAL COMPONENT DATA

# FBP 12+1 3069408 PHOENIX CONTACT Dummy plug

**Brand: PHOENIX CONTACT | Manufacturer Part Number: FBP 12+1**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | FBP 12+1 |
| Catalog number | 3069408 |
| Category | Test plug for terminal blocks |
| Minimum order | 5 Pcs |
| Document ID | EO-92559E3222 |
| Generated | 2026-11-18 |

## Product Overview

Dummy plug
Blind cap, number of poles: 13, color: orange
Blind connector, number of poles: 13, colour: orange

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Enclosures connectivity |

## Additional Product Information

Key Commercial Data
Orderkey 3069408
Packing unit 5 pc
Minimum order quantity 5 pc
Note Made to Order (non-returnable)
Catalog page Page 593 (C-1-2017)
GTIN 4046356749787
Weight per Piece (excluding packing) 120.540 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Number of positions 13
Color orange
Insulating material PA

Flammability rating according to UL 94 V0
Result of surge voltage test Test passed
Surge voltage test setpoint 4.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.2 kg
6 mm2/ 1.4 kg
10 mm² / 2 kg
Tensile test result Test passed
Conductor cross section tensile test 0.2 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 6 mm²
Tractive force setpoint 80 N
Conductor cross section tensile test 10 mm²
Tractive force setpoint 90 N
Result of tight fit on support Test passed
Tight fit on carrier Panel cutout
Setpoint 5 N
Result of voltage-drop test Test passed
Requirements, voltage drop <= 3.2 mV
Result of temperature-rise test Test passed
Short circuit stability result Test passed
Conductor cross section short circuit testing 4 mm²
Short-time current 300 A
Conductor cross section short circuit testing 4 mm²
Short-t...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBP 12+1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.