INDUSTRIAL COMPONENT DATA

E-WM (EX23)R YE 1234233 PHOENIX CONTACT Marking foil, Roll, yellow, unlabeled, labelable with: THERMOMARK E...

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WM (EX23)R YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	E-WM (EX23)R YE
Catalog number	1234233
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-D81BF55FB0
Generated	2026-11-19

Product Overview

Marking foil, Roll, yellow, unlabeled, labelable with: THERMOMARK E.WIRE, cable diameter range: 1.8 ... 5.6 mm, mounting class: solder, Number of individual indexes: 1, length. Roll: 90 m, text field height: 23 mm
Marking Sheet, Roll, Yellow, Unlabeled, Labelable with: THERMOMARK E.WIRE, Mounting Class: Welding, Cable Diameter Range: 1.8 ... 5.6 mm, usable area: 3 marking fields with variable height x 22.1 mm, long. Roll: 100 m
Marking foil, Roll, yellow, unlabeled, labelable with: THERMOMARK E.WIRE, THERMOMARK E.300 (D)/600 (D), mounting class: weld, cable diameter range: 1.8 ... 5.6 mm, usable area: 3 marking fields with variable height x 22.1 mm, long. Roll: 90 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataItem PropertiesProduct Type Unlabeled conductor marker
Signage
Marking technology Thermal Transfer for Rolls
Connection dataAWG Conductor Section (Converted according to IEC)
DimensionsWidth 22.4 mm
Roll Length 90.00 m
Material DataColour yellow
Material PET + Hot Melt Thermoplastic Adhesive
Substances contained Silicone-free and halogen-free

Cable/LineCable Outer Diameter 1.8 mm ... 5.6 mm
Environmental and life-life conditionsTesting for substances that are harmful to varnish wetting
Testing for substances harmful to varnish wetting (LABS conformity) VW PV 3.10.7:2005-02
Result Approved Test
Scratch test to determine scratch resistance
Test Specification DIN EN ISO 1518-1:2019-10 (in accordance with the law)
Demand >= 5 N
Result Approved Test
tesafilm tape test
Test Specification DIN EN ISO 2409:2013 (conforming)
Result Approved Test
Resistance to ultraviolet rays
Test Specification DIN EN ISO 4892-2:2013-06 (conformity)
Result Approved Test
Duration of the trial 96 h
Procedure Artificial radiation with xenon arc lamp
Temperature-controlled storage
Test Specification DIN EN 60068-2-2 (VDE 0468-2-2):2008-05
Result Approved Test
Duration 96 h
Test Temperature 80 °C
Changing Climate Test of Condensed Water with Sulphur Dioxide Atmosphere
Test Specification DIN 50018:2013-05
Result Approved Test
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Test Specification DIN EN 60068-2-11:2000-02
Result Approved Test
Duration of the trial 96 h
Environmental conditions
Ambi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WM (EX23)R YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.