INDUSTRIAL COMPONENT DATA

E-WML 12 (25X19)R 1199677 PHOENIX CONTACT Cable wrapping label, Roll, white, unlabelled, labelable with: THE..

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WML 12 (25X19)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	E-WML 12 (25X19)R
Catalog number	1199677
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-E00E594E20
Generated	2026-11-18

Product Overview

Cable wrapping label, Roll, white, unlabelled, labelable with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting class: glued, cable diameter range: 6.1 ... 12.1 mm, usable area: 25.4 x 19.1 mm, number of individual indexes: 2750
Cable wrap label, Roll, white, blank, can be labelled with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting type: glue, cable diameter: 6.1 ... 12.1 mm, Marking field size: 25.4 x 19.1 mm, Number of individual tags: 2750

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataArticle featuresProduct Type Blank conductor markers
Execution Label
Marking
Number of individual cards 2750
Number of cards per line 1
Marking technology Thermal transfer for rolls
Connection dataConductor cross-section AWG (converted according to IEC)
dimensionswidth 25.4 mm
length 57.2 mm
Material informationRoHS compliant Yes
Glue Acrylate

Color white
Material PVC
Substances silicone-free
Cable/LineConductor Outer Diameter 12.1 mm
6.1 mm ... 12.1 mm
Environmental and electrical life conditionsScratch test for the determination of scratch resistance
Test Specification DIN EN ISO 1518-1:2019-10 (in compliance)
Application >= 5 N
Result Test passed
Adhesive tape test
Test Specification DIN EN ISO 2409:2013 (in conformity)
Result Test passed
UV resistance
Test Specification DIN EN ISO 4892-2:2013-06 (in accordance with)
Result Test passed
Duration of the trial 96 h
Procedure Artificial irradiation with xenon arc lamp
Temperature-controlled storage
Test Specification IEC 60068-2-2:2007-07
Result Test passed
Duration 96 h
Test Temperature 100 °C
Thermal stability
Test Specification ANSI/UL 969-2018:03 (compliant)
Duration of the trial 240 h
Rating 100 °C (121 °C) Test passed
Resistance to chemicals, oils and fuels
Test Specification ISO 175:2010 (in compliance)
Duration of the trial 168 h
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Test passed
Brackish water (350 g/l)
[CAS No. -] Test passed
Diesel
[CAS No. 68476-34-6] Test passed
IRM 901 Test passed
IRM 902 T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WML 12 (25X19)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.