INDUSTRIAL COMPONENT DATA

E-WML 14 (25X19)R 1199679 PHOENIX CONTACT Cable wrapping label, Roll, white, unlabelled, labelable with: THE..

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WML 14 (25X19)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	E-WML 14 (25X19)R
Catalog number	1199679
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-48AE8DEE57
Generated	2026-11-19

Product Overview

Cable wrapping label, Roll, white, unlabelled, labelable with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting class: glued, cable diameter range: 6.1 ... 14.2 mm, usable area: 25.4 x 19.1 mm, number of individual indexes: 2450
Wire-wrap label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting type: adhesive, cable diameter range: 6.1 ... 14.2 mm, lettering field size: 25.4 x 19.1 mm, Number of individual labels: 2450

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking
Type Label
Marking
Number of individual labels 2450
Number of individual labels per row 1
Identification technology Thermal transfer for rolls
Connection dataCross section AWG (converted acc. to IEC)
DimensionsWidth 25.4 mm
Length 63.5 mm
Material specificationsRoHS compliant yes

Adhesive Acrylic
Color white
Material PVC
Components Silicone-free
Cable/lineExternal cable diameter 14.2 mm
6.1 mm ... 14.2 mm
Environmental and real-life conditionsScratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Specification IEC 60068-2-2:2007-07
Result Test passed
Duration 96 h
Temperature for testing 100 °C
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 100 °C (121 °C) Test passed
Specification ISO 175:2010 (following)
Test duration 168 h
Diesel
[CAS No. 68476-34-6] Test passed
IRM 901 Test passed
IRM 902 Test passed
Testing in a condensation changing climate in the presence of sulfur dioxide
Specification DIN 50018:2013-05
Result Test passed
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Specification DIN EN 60068-2-11:2000-02
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WML 14 (25X19)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.