INDUSTRIAL COMPONENT DATA

E-WML 14 (25X19)R YE 1199681 PHOENIX CONTACT Cable wrapping label, Roll, yellow, unlabelled, labelable with:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: E-WML 14 (25X19)R YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	E-WML 14 (25X19)R YE
Catalog number	1199681
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-A0E83D735C
Generated	2026-11-19

Product Overview

Cable wrapping label, Roll, yellow, unlabelled, labelable with: THERMOMARK E.WRAP, THERMOMARK E.300 (D)/600 (D), mounting class: glued, cable diameter range: 6.1 ... 14.2 mm, usable area: 25.4 x 19.1 mm, number of individual indexes: 2450

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataItem PropertiesProduct Type Unlabeled conductor marker
Execution Label
Signage
Number of Individual Indexes 2450
Number of individual labels per line 1
Marking technology Thermal Transfer for Rolls
Connection dataAWG Conductor Section (Converted according to IEC)
DimensionsWidth 25.4 mm
Longitude 63.5 mm
Material DataRoHS Compliant Yes
Adhesive Acrylate
Colour yellow
Material PVC

Substances contained Silicone-free
Cable/LineCable Outer Diameter 14.2 mm
6.1 mm ... 14.2 mm
Environmental and life-life conditionsScratch test to determine scratch resistance
Test Specification DIN EN ISO 1518-1:2019-10 (in accordance with the law)
Demand >= 5 N
Result Approved Test
tesafilm tape test
Test Specification DIN EN ISO 2409:2013 (conforming)
Result Approved Test
Resistance to ultraviolet rays
Test Specification DIN EN ISO 4892-2:2013-06 (conformity)
Result Approved Test
Duration of the trial 96 h
Procedure Artificial radiation with xenon arc lamp
Temperature-controlled storage
Test Specification IEC 60068-2-2:2007-07
Result Approved Test
Duration 96 h
Test Temperature 100 °C
Temperature resistance
Test Specification ANSI/UL 969-2018:03 (Compliant)
Duration of the trial 240 h
Rating 100 °C (121 °C) Approved Test
Resistance to chemicals, oils and fuels
Test Specification ISO 175:2010 (Conformity)
Duration of the trial 168 h
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Approved Test
Salt water (350 g/l)
[CAS No. -] Approved Test
Diesel
[CAS No. 68476-34-6] Approved Test
MRI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E-WML 14 (25X19)R YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.