
INDUSTRIAL COMPONENT DATA

EBL 4- 5 2303161 PHOENIX CONTACT Insertion bridge

Brand: PHOENIX CONTACT | Manufacturer Part Number: EBL 4-5



Manufacturer	PHOENIX CONTACT
MPN / Reference	EBL 4-5
Catalog number	2303161
Category	Cross-connector for terminal block
Minimum order	10 Pcs
Document ID	EO-4A21AED3B1
Generated	2026-11-19

Product Overview

Insertion bridge
Bridge comb, pitch: 5.2 mm, color: gray
Insertion bridge, pitch: 5.2 mm, number of positions: 4, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Insertion bridge
Number of positions 4
Pitch 5.2 mm
Data management status
Article revision 01
DimensionsPitch 5.2 mm
Material specificationsColor gray (RAL 7042)
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EBL 4-5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.