INDUSTRIAL COMPONENT DATA

ECS-B-122X109-L-UV1-V 1054714 PHOENIX CONTACT Snap-in locking vented enclosure of the ECS Family. IP66/67/69..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-B-122X109-L-UV1-V



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-B-122X109-L-UV1-V
Catalog number	1054714
Category	Extruded profile modular housing
Minimum order	5 Pcs
Document ID	EO-3F4D75E73C
Generated	2026-11-19

Product Overview

Snap-in locking vented enclosure of the ECS Family. IP66/67/69 rated when mated with associated faceplate. Color: Black (9005), Width: 172 mm, Height: 116 mm, Depth: 64
Ventilated housing from the ECS family, locking by snapping. IP66/67/69 protection rating in case of combination with the corresponding faceplate. Colour: black (9005), width: 172 mm, height: 116 mm, depth: 64 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1054714
Packing unit 1 pc
GTIN 4055626690827
Weight per Piece (excluding packing) 9.600 g
Custom tariff number 85389099
Country of origin US (United States)
Drawings
Measurements
Ambient conditions

Packaging information
Environmental Product Compliance
Item properties
Material specifications
PCB data
Standards and regulations
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Type ECS-B-122X109-L-UV1-V
Order No. 1054714
Type Snap-in locking
Mounting type Wall or panel mount. Pole mount with accessory.
Ventilation integrated pressure compensation membrane
Back to topMeasurements
Dimensional drawing
Width [w] 172 mm
Height [h] 116 mm
Depth [d] 64 mm
Back to topMaterial specifications
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material PC (polycarbonate)
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Back to topPCB data
PCB thickness 1.59 mm ... 2.36 mm
Back to topPackaging information
Pieces per package 5
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topEnvironmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 4.0 27180401
eCl@ss 4.1 27180401
eCl@ss 5.0 27180505
eCl@ss 5.1 27180505
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 2718270...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-B-122X109-L-UV1-V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.