INDUSTRIAL COMPONENT DATA

ECS-P-122X169-L-UV-1M12 GY 1050385 PHOENIX CONTACT Snap-in locking one female M12 faceplate of the ECS Famil..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-P-122X169-L-UV-1M12 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-P-122X169-L-UV-1M12 GY
Catalog number	1050385
Category	Extruded profile modular housing
Minimum order	5 Pcs
Document ID	EO-EC390D91B8
Generated	2026-11-19

Product Overview

Snap-in locking one female M12 faceplate of the ECS Family. IP66/67/69 rated when mated with associated enclosure. Color: Grey (7042), Width: 196 mm, Height: 34 mm, Depth: 62 mm
Faceplate of the ECS family, SPEEDCON M12 female connector (1 units), socket lock. IP66/67/69 protection rating in combination with the corresponding box. Color: gray (7042); width: 196 mm; height: 34 mm; Depth: 62 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1050385
Packing unit 1 pc
GTIN 4055626666921
Weight per Piece (excluding packing) 128.000 g
Custom tariff number 85389099
Country of origin US (United States)
Drawings
Measurements
Ambient conditions
Packaging information
Environmental Product Compliance

Item properties
Material specifications
PCB data
Standards and regulations
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Type ECS-P-122X169-L-UV-1M12 GY
Order No. 1050385
Type Snap-in locking
Connection 1x M12 nut
Mounting type Mechanical latch to base
Back to topMeasurements
Dimensional drawing
Width [w] 196 mm
Height [h] 34 mm
Depth [d] 62 mm
Back to topMaterial specifications
Color (RAL) gray (7042)
Flammability rating according to UL 94 V0
Housing material PC (polycarbonate)
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Back to topPCB data
Number of PCB holders 1
Back to topPackaging information
Pieces per package 5
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topEnvironmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Back to topClassifications
eCl@ss
eCl@ss 4.0 27180401
eCl@ss 4.1 27180401
eCl@ss 5.0 27180505
eCl@ss 5.1 27180505
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 271...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-P-122X169-L-UV-1M12 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.