INDUSTRIAL COMPONENT DATA

ECS-P-122X169-S-UV-B GY 1050382 PHOENIX CONTACT Screw locking blank faceplate of the ECS Family. IP66/67/69 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-P-122X169-S-UV-B GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-P-122X169-S-UV-B GY
Catalog number	1050382
Category	Extruded profile modular housing
Minimum order	5 Pcs
Document ID	EO-0F8BF8C1AD
Generated	2026-11-19

Product Overview

Screw locking blank faceplate of the ECS Family. IP66/67/69 rated when mated with associated enclosure. Color: Grey (7042), Width: 163 mm, Height: 30 mm, Depth: 62 mm
ECS family faceplate, empty, screw lock. IP66/67/69 protection rating in case of combination with the corresponding housing. Colour: grey (7042), width: 163 mm, height: 30 mm, depth: 62 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1050382
Packing unit 1 pc
GTIN 4055626665245
Weight per Piece (excluding packing) 116.000 g
Custom tariff number 85389099
Country of origin US (United States)
Drawings
Measurements
Ambient conditions
Packaging information
Environmental Product Compliance

Item properties
Material specifications
PCB data
Standards and regulations
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Type ECS-P-122X169-S-UV-B GY
Order No. 1050382
Type Screw locking
Connection without
Mounting type Screw locking
Back to topMeasurements
Dimensional drawing
Width [w] 163 mm
Height [h] 30 mm
Depth [d] 62 mm
Back to topMaterial specifications
Color (RAL) gray (7042)
Flammability rating according to UL 94 V0
Housing material PC (polycarbonate)
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Back to topPCB data
Number of PCB holders 1
Back to topPackaging information
Pieces per package 5
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topEnvironmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 4.0 27180401
eCl@ss 4.1 27180401
eCl@ss 5.0 27180505
eCl@ss 5.1 27180505
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 3.0 EC001031

ETIM 4.0 EC001031...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-P-122X169-S-UV-B GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.