INDUSTRIAL COMPONENT DATA

ECS-P-122X169-S-UV1-1M1FM12 1091841 PHOENIX CONTACT ECS family faceplate, ready for integration of one M12 m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-P-122X169-S-UV1-1M1FM12



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-P-122X169-S-UV1-1M1FM12
Catalog number	1091841
Category	Extruded profile modular housing
Minimum order	5 Pcs
Document ID	EO-8A81285493
Generated	2026-11-19

Product Overview

ECS family faceplate, ready for integration of one M12 male and female connectors, screw locking, rated IP66/67/69 when combined with ECS housing, Color: Black (9005), Width: 163 mm, Height: 30 mm, Depth: 62 mm
Faceplate with SPEEDCON M12 connectors (1 male, 1 female), screw lock. IP66/67/69 protection rating in combination with the corresponding housing, width: 163 mm, height: 30 mm, depth: 62 mm, colour: black (9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1091841
Packing unit 1 pc
GTIN 4055626906324
Weight per Piece (excluding packing) 132.000 g
Custom tariff number 85389099
Country of origin US (United States)
Drawings
Measurements
Ambient conditions
Packaging information
Environmental Product Compliance

Item properties
Material specifications
PCB data
Standards and regulations
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Type ECS-P-122X169-S-UV1-1M1FM12
Order No. 1091841
Type Screw locking
Mounting type Screw locking
Back to topMeasurements
Dimensional drawing
Width [w] 163 mm
Height [h] 30 mm
Depth [d] 62 mm
Back to topMaterial specifications
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material PC (polycarbonate)
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 100 °C
Back to topPCB data
Number of PCB holders 1
PCB thickness 1.59 mm ... 2.36 mm
Back to topPackaging information
Pieces per package 5
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topEnvironmental Product Compliance
REACh SVHC Lead 7439-92-1
Back to topClassifications
eCl@ss
eCl@ss 4.0 27180401
eCl@ss 4.1 27180401
eCl@ss 5.0 27180505
eCl@ss 5.1 27180505
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 3.0 EC001031
ETIM 4.0 EC001031
ETIM 5.0 EC000058

ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to topUNSPSC
UNSPSC 6.01 31261501....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-P-122X169-S-UV1-1M1FM12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.