INDUSTRIAL COMPONENT DATA

ECS-SKT-122X169-S-UV-9005 1457013 PHOENIX CONTACT Empty box for wall or pole mounting, black 9005, modular e..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ECS-SKT-122X169-S-UV-9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	ECS-SKT-122X169-S-UV-9005
Catalog number	1457013
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-DFF244B2A5
Generated	2026-11-19

Product Overview

Empty box for wall or pole mounting, black 9005, modular electronics enclosure with faceplate, for outdoor applications, degree of protection: IP66/67/69, width 164 mm, height 180 mm, depth 64 mm, printed circuit board surface 13 160 mm² Empty enclosure for wall or mast mounting, black (9005), modular electronics housing with front plate, for outdoor applications, degree of protection: IP66/IP67/IP69, width: 164 mm, height: 180 mm, depth: 64 mm, PCB surface: 13160 mm2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.
Product propertiesProduct type Stackable housing set
Type Screw locking mechanism
Housing type outdoor housings
Housing series ECS
Ventilation integrated pressure compensation membrane
DimensionsDimensional drawing
Width 163.8 mm
Height 179.8 mm
Depth 62.1 mm
PCB design

PCB thickness 1.57 mm ... 2.36 mm
Material specificationsColor black (9005)
Flammability rating according to UL 94 V0
Impact strength IK08
Housing material PC (polycarbonate)
Environmental and real-life conditionsPower dissipation single housing for 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 19 W
Ambient conditions
Max. NEMA code to attain 6
Impact strength IK08
Ambient temperature (operation) -40 °C ... 100 °C
Ambient temperature (storage/transport) -40 °C ... 100 °C
PCB dataNumber of PCB holders 1
Type of PCB mount Bolt mounting
Thickness of the PCB 1.57 mm ... 2.36 mm
MountingMounting type Wall or panel mount. Pole mount with accessory.
Packaging specificationsType of packaging packed in cardboard
Outer packaging type Carton

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ECS-SKT-122X169-S-UV-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.