INDUSTRIAL COMPONENT DATA

EEM-MB371 2907955 PHOENIX CONTACT Multi-functional energy measuring device without display with direct Rogow..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EEM-MB371



Manufacturer	PHOENIX CONTACT
MPN / Reference	EEM-MB371
Catalog number	2907955
Category	Multifunction measuring instrument
Minimum order	1 Pcs
Document ID	EO-5F8F5E530B
Generated	2026-11-18

Product Overview

Multi-functional energy measuring device without display with direct Rogowski connection and integrated Modbus/TCP interface for measuring electrical parameters in low-voltage installations up to 690 V.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2907955
Packing unit 1 pc
Catalog page Page 203 (C-5-2019)
GTIN 4055626498348
Weight per Piece (excluding packing) 400.000 g
Custom tariff number 90303100
Country of origin DE (Germany)
Dimensions
Input data
General
Connection data 2
Standards and Regulations
Classifications

Ambient conditions
Output data
Connection data
UL data
Environmental Product Compliance
Dimensions
Width 90 mm
Height 80 mm
Depth 64 mm
Back to topAmbient conditions
Ambient temperature (operation) -10 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Maximum altitude <= 2000 m
Max. permissible relative humidity (operation) <= 95 % (non-condensing)
Degree of protection IP20 (Housing)
Back to topInput data
Measuring principle True r.m.s. value measurement
Acquisition of harmonics up to 63rd harmonic
Measured value AC sine (50/60 Hz)
Input name Voltage measuring input V1, V2, V3
Input voltage range 35 V AC ... 690 V AC (Phase/Phase)
20 V AC ... 400 V AC (Phase/neutral conductor)
60 V AC ... 2000000 V AC (primary)
60 V AC ... 400 V AC (secondary)
Surge voltage capacity 760 V AC (Phase/Phase)
Precision 0.2 %
Input name Current measurement RC1, RC2, RC3
Input current 4000 A
Response threshold from measuring range nominal value 5 A
Precision < 1 %
1 %
Reactive power (IEC 62053-23) Class 2
Description of the input Digital input in accordance with IEC/EN 61131-2 (type 3)
Number 1
Voltage input signal 0 V DC ... 30 V DC
Current input signal 2 mA ... 15 mA
Back to top...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EEM-MB371 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.