INDUSTRIAL COMPONENT DATA

EH 17,5 F-FP/ABS-PC GY7035 1074611 PHOENIX CONTACT DIN rail housing, Filler plug for unoccupied terminal poi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 17,5 F-FP/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 17,5 F-FP/ABS-PC GY7035
Catalog number	1074611
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-D9329D72D0
Generated	2026-11-19

Product Overview

DIN rail housing, Filler plug for unoccupied terminal points, with vents, width: 16.3 mm, height: 13.67 mm, depth: 33.39 mm, color: light gray (7035)
Rail box, Blank plug for non-equipped terminal points (flat design), with ventilation slits, width: 16.3 mm, height: 33.39 mm, depth: 13.67 mm, colour: light grey (7035)
DIN rail housing, Filler plug for unoccupied terminal points (flat design), with vents, width: 16.3 mm, height: 33.39 mm, depth: 13.67 mm, color: light gray (similar RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Product propertiesProduct type Filler plug
Housing type DIN rail housing
Housing series EH
Product family EH..F..ABS-PC..
Type Filler plug for unoccupied terminal points (flat design)
Ventilation openings present yes
Data management status
Article revision 00
DimensionsDimensional drawing

Width 16.3 mm
Height 33.39 mm
Depth 13.67 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
Housing material ABS-PC
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 80 °C
Relative humidity (storage/transport) 95 %
PCB dataType of PCB mount Slot
MountingMounting type Latching with upper housing part

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 17,5 F-FP/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.