INDUSTRIAL COMPONENT DATA

EH 45 F-C DS/ABS-PC GY7035 1074966 PHOENIX CONTACT DIN rail housing, Upper part, connection opening on both ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 45 F-C DS/ABS-PC GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	EH 45 F-C DS/ABS-PC GY7035
Catalog number	1074966
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-FE1B53F5AF
Generated	2026-11-19

Product Overview

DIN rail housing, Upper part, connection opening on both sides, width: 45.1 mm, height: 74.65 mm, depth: 36.95 mm, color: light gray (7035)
Rail box, Housing top, flat design, connection hole on both sides, width: 45.1 mm, height: 74.65 mm, depth: 36.95 mm, color: light gray (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1074966
Packing unit 1
GTIN 4055626777801
Custom tariff number 85389099
Drawings
Dimensions
Ambient conditions
General information
Standards and regulations
Item properties
Material data

PCB data
Packaging information
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Upper part of housing
Type EH 45 F-C DS/ABS-PC GY7035
Order No. 1074966
Housing type DIN rail housing
Housing series EH
Type Upper part
Max. IP code to attain IP20
Mounting type Snap in
Ventilation openings present no
Back to topDimensions
Dimensional drawing
Width [w] 45.1 mm
Height [h] 74.65 mm
Depth [d] 36.95 mm
Depth from base support surface [d] 19.95 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS-PC
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 80 °C
Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)
Back to topPCB data
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Back to topPackaging information
Pieces per package 10
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.0 27180506
eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 45 F-C DS/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.