INDUSTRIAL COMPONENT DATA

# EH 67,5 F-C CS/ABS-PC GY7035 1074947 PHOENIX CONTACT DIN rail housing, Upper part, Without connection openin..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: EH 67,5 F-C CS/ABS-PC GY7035**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | EH 67,5 F-C CS/ABS-PC GY7035 |
| Catalog number | 1074947 |
| Category | Extruded profile modular housing |
| Minimum order | 1 Pcs |
| Document ID | EO-285DD87A45 |
| Generated | 2026-11-19 |

## Product Overview

DIN rail housing, Upper part, Without connection opening, with vents, width: 67.6 mm, height: 74.65 mm, depth: 36.95 mm, color: light gray (7035)
Rail box, Top of housing, flat design, no connection hole, width: 67.6 mm, height: 74.65 mm, depth: 36.95 mm, colour: light grey (7035)
DIN rail housing, Upper housing part, flat design, no connection opening, width: 67.6 mm, height: 74.65 mm, depth: 36.95 mm, color: light gray (similar RAL 7035)

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Product propertiesProduct type Upper housing part
Housing type DIN rail housing
Housing series EH
Product family EH..F..ABS-PC..
Type Upper housing part, flat design, no connection opening
Ventilation openings present yes
Data management status
Article revision 00
DimensionsDimensional drawing

Width 67.6 mm
Height 74.65 mm
Depth 36.95 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
Housing material ABS-PC
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 80 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 80 °C
Relative humidity (storage/transport) 95 %
PCB dataType of PCB mount Latching
MountingMounting type Snap in

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EH 67,5 F-C CS/ABS-PC GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.