INDUSTRIAL COMPONENT DATA

# ME MAX 45 3-3 KMGY 2713913 PHOENIX CONTACT Electronic housing

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 45 3-3 KMGY**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ME MAX 45 3-3 KMGY |
| Catalog number | 2713913 |
| Category | Electronic enclosure |
| Minimum order | 10 Pcs |
| Document ID | EO-F6A92A34E3 |
| Generated | 2026-11-19 |

## Product Overview

Electronic housing
Rail box, Complete housing with metal pin, tall design, with ventilation slits, width: 45.2 mm, height: 99 mm, depth: 113.65 mm, colour: luminous grey (7035), cross-bridge: Bus connector for rail (optional), number of poles cross connector: 5

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Key Commercial Data
Orderkey 2713913
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 688 (C-1-2013)
GTIN 4017918936266
Weight per Piece (excluding packing) 72.830 g
Custom tariff number 85389099
Country of origin DE (Germany)
Item properties
Brief article description Electronic housing
Type ME MAX 45 3-3 KMGY
Order No. 2713913

Housing type DIN rail housing
Type Tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Number of levels 3
Ventilation openings present yes
Max. number of positions 60 (pitch: 3.5 mm)
48 (pitch: 5 mm)
36 (pitch: 7.25 mm/7.5 mm)
Dimensions
Dimensional drawing
Width [ w ] 45 mm
Height [ h ] 99 mm
Depth [ d ] 114.5 mm
Depth from top edge of DIN rail [ d ] 107 mm
Material data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polyamide
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
PCB data
Number of PCB holders 2
PCB thickness 1.4 mm ... 1.8 mm
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Power dissipation, single housing at 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 8.2 W
Power dissipation, single housing at 30 °C
Ambient temperature 30 °C
Reduction factor 0.91
Mounting position vertical
Power diss...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 45 3-3 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.