INDUSTRIAL COMPONENT DATA

ELR H3-IES-PT-24DC/500AC-06-T 2906061 PHOENIX CONTACT Hybrid motor starter

Brand: PHOENIX CONTACT | Manufacturer Part Number: ELR H3-IES-PT-24DC/500AC-06-T



Manufacturer	PHOENIX CONTACT
MPN / Reference	ELR H3-IES-PT-24DC/500AC-06-T
Catalog number	2906061
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-F20A95D459
Generated	2026-11-19

Product Overview

Hybrid motor starter
Hybrid boot controller; Functions: Starting Engine Engine Protection, Emergency Stop, Increased Resistance to Transient Voltages; input: 24 VDC; Output: 3~, 500 VAC, 600 mA; Connection Type: Push-In Connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2906061
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626024707
Weight per Piece (excluding packing) 269.600 g
Custom tariff number 85371098
Country of origin DE (Germany)
Device supply
Rated control circuit supply voltage US 24 V DC
Control supply voltage range 19.2 V DC ... 30 V DC
Rated control supply current IS 40 mA
Type of protection Surge protection

Reverse polarity protection
Input data
Input name Control input
Rated actuating voltage UC 24 V DC
Triggering voltage range 19.2 V DC ... 30 V DC
Rated actuating current IC 5 mA
Switching threshold 9.6 V (“0” signal)
19.2 V (“1” signal)
Switching level < 5 V DC (For EMERGENCY STOP)
Typical turn-off time < 30 ms
Type of protection Reverse polarity protection
Output data load output
Output name AC output
Rated operating voltage Ue 500 V AC
Operating voltage range 42 V AC ... 550 V AC
Rated operating current Ie 0.6 A (AC-51)
0.6 A (AC-53a)
Mains frequency 50/60 Hz
Load current range 75 mA ... 600 mA (see to derating)
Trigger characteristic in acc. with IEC 60947-4-2 Class 10A
Cooling time 20 min.
Leakage current 0 mA
Type of protection Surge protection
Output data reply output
Output name Acknowledge output
Note Confirmation: floating change-over contact, signal contact
Contact type 1 PDT
Switching capacity according to IEC 60947-5-1 3 A (230 V, AC15)
2 A (24 V, DC13)
General
Switching frequency <= 2 Hz (Load-dependent)
Mounting position vertical (horizontal DIN rail, motor output....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ELR H3-IES-PT-24DC/500AC-06-T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.